



Clamp system, Type PPU

Profile clamp set with lift-off prevention for pipe bearings, bottom-ventilation	
Material:	S235 or similar, threaded parts 8.8 / 8, hot-dip galvanized
Camber:	M12 - 30 Nm
Joining profile width:	85 - 300 mm, other profiles on request

Article no.	joining profile		thread rod	G	X	loads [kN]		weight
	A	B				F _z	F _y	
PPU-120/12-R-F	085 - 120	8 - 20	200	50	26	22,0	10,0	2,9
PPU-160/12-R-F	130 - 160	8 - 20	240	50	26	19,0	9,0	3,0
PPU-200/12-R-F	170 - 200	8 - 20	280	50	26	16,0	8,0	3,1
PPU-240/12-R-F	210 - 240	8 - 20	320	50	26	13,0	7,0	3,3
PPU-300/12-R-F	250 - 300	8 - 20	400	50	26	10,0	6,0	3,4

Clamp system, Type PPU-PA, PPU-PT

Profile clamp set with lift-off prevention for pipe bearings, bottom-ventilation, with PA6/PTFE-support plate	
Material:	S235 or similar, threaded parts 8.8 / 8, hot-dip galvanized, PA6/PTFE-support plate -35°C to +80°C
Camber:	M12 - 30 Nm
Joining profile width:	85 - 200 mm, other profiles on request

Article no.	joining profile		thread rod	G	X	loads [kN]		weight
	A	B				F _z	F _y	
PPU-PA-120/12-R-F	085 - 120	8 - 20	200	50	26	22,0	10,0	2,9
PPU-PA-160/12-R-F	130 - 160	8 - 20	240	50	26	19,0	9,0	3,0
PPU-PA-200/12-R-F	170 - 200	8 - 20	280	50	26	16,0	8,0	3,1
PPU-PT-120/12-R-F	085 - 120	8 - 20	200	50	26	22,0	10,0	2,9
PPU-PT-160/12-R-F	130 - 160	8 - 20	240	50	26	19,0	9,0	3,0
PPU-PT-200/12-R-F	170 - 200	8 - 20	280	50	26	16,0	8,0	3,1

Ordering example: PPU-200/12-R-F

- Hot-dip galvanized
- Material S235 or similar
- Diameter of thread rods: Ø12
- Beam width 170 - 200 mm e.g. HEA 200
- Profile clamp set with lift-off prevention, without Sliding plate

* Notes: A middle piece can be delivered for PPU with profiles > 240 mm width, combined with short supports.
 Please ask for PK-AM-12.

Constructive Notice: If using pipe supports as hanging version, the loads will halve (50%).